

## AMENDMENTS

### Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (currently amended) A method of measuring mass flow of a first gas component in a gas consisting of ~~two~~ one or more known gas components, which gas flows in a pipe in which one or more measurement devices (440, 450, 460, 461, 462, 465; 540, 550, 560, 561, 562, 565; 635, 640, 660, 661, 662, 665) is/are arranged in connection with the pipe, where a tubular body (410, 510, 610) is incorporated in connection with the pipe, said method comprising the following steps:

- determination of one or more gas parameters of the gas by means of the measurement device(s) (440, 450, 460, 461, 462, 465; 540, 550, 560, 561, 562, 565; 635, 640, 660, 661, 662, 665),

- determination of the mass flow of the one gas component by means of the determination of the one or more gas parameters,

~~characterised in that~~ wherein the determination of the one or more gas parameters comprises a continuous determination of all of those of the gas parameters that are used in the determination of the mass flow of the first gas component and which may vary considerable as a function of the gas composition, pressure and/or temperature, ~~and~~ wherein the step of determination of one or more gas parameters by means of measurement devices comprise:

- determination of the gas temperature  $T_1$  at the inlet of the tubular body;

- supply of a given amount of energy E to the gas in the tubular body (410; 510; 610), and

- determination of the gas temperature  $T_2$  at the outlet of the tubular body;

wherein ~~that~~ the one or more measurement device(s) (440, 450, 460, 461, 462, 465; 540, 550, 560, 561, 562, 565; 635, 640, 660, 661, 662, 665) comprise a volume percentage measurement instrument (440; 540; 640) arranged to measure the volume percentage of at least the first gas component in the gas in order to determine the gas composition for use in the determination of the mass flow of the first gas component, the volume percentage measurement instrument (440; 540; 640) being arranged in or in immediate vicinity of the tubular body (410; 510; 610).

2. (cancelled)

3. (currently amended) A method according to claim 1, characterised in that ~~the in connection with the pipe~~ a tubular body (410; 510; 610) ~~is incorporated, which~~ is surrounded by an insulating material (430; 530; 630), that the measurement device(s) (440, 450, 460, 461, 462, 465; 540, 550, 560, 561, 562, 565; 635, 640, 660, 661, 662, 665), that are used for determining the one or more gas parameters comprise ~~a volume percentage measurement instrument (440; 540; 640) and~~ two temperature measurement instruments (460, 465 ; 560, 565; 660, 665), and where ~~wherein the volume percentage measurement instrument (440; 540; 640) is arranged in or in immediate vicinity of the tubular body (410; 510; 610) and wherein~~ the one temperature measurement instrument (460; 560; 660) is arranged at the inlet of the tubular body (410; 510; 610) and the second temperature measurement instrument (465; 565; 665) is arranged at the outlet of the tubular body (410; 510; 610).

4. (cancelled)

5. (previously presented) A method according to claim 1, characterised in that those of the gas parameters that are determined continuously and that partake in the determination of the mass flow consist of the gas composition and the gas temperature T1 at the inlet of the tubular body and the gas temperature T2 at the outlet of the tubular body.

6. (withdrawn) A method according to claim 1, characterised in that the measurement devices comprise a pressure differential measuring instrument (450; 550; 640) and a volume percentage measurement instrument (440; 540; 640); and in that those of the gas parameters that are determined continuously and partake in the determination of the mass flow of the first gas

component comprise pressure differential across a restriction and the volume percentage of the first gas component.

7. (withdrawn) A method according to claim 6, characterised in that the measurement devices moreover comprise a temperature measuring instrument (460, 461, 462, 465; 560, 561, 562, 565; 660, 661, 662, 665) and that those of the gas parameters that are determined continually and partake in the determination of the mass flow of the first gas component moreover comprise the gas temperature.
8. (withdrawn) A method according to claim 6, characterised in that those of the gas parameters that are determined continually and partake in the determination of the mass flow comprise the gas density.
9. (withdrawn) A method according to claim 1, characterised in that the measurement devices comprise a hotwire and a volume percentage measurement instrument.
10. (withdrawn) A method according to claim 9, characterised in that the measurement devices also comprise a temperature measurement instrument.
11. (withdrawn) A method according to claim 9, characterised in that those of the gas parameters that are determined continuously and partake in the determination of the mass flow comprise one or more of the following: the viscosity of the gas, the heat capacity of the gas, the heat conductivity of the gas, the density of the gas, and the temperature of the gas, the volume percentage of the first gas component.
12. (previously presented) The method according to claim 1 for the determination of the mass flow of a first gas component being in saturation state.
13. (previously presented) The method according to claim 12, wherein the first gas component being in saturation state is water vapour.
14. (previously presented) The method according to claim 1 for the determination of the mass flow of a first gas component in a biogas.

15. (previously presented) A mass flow measurement device for measuring a first gas component in a gas consisting of one or more known gas components, wherein the mass flow measurement device performs the method according to claim 1.

16. (currently amended) A mass flow measurement device according to claim 15, wherein the ~~mass flow measurement device comprises~~ a tubular body (410; 510; 610) surrounded by an insulating material (430; 530; 630), ~~the which~~ tubular body (410; 510; 610) being is configured for being connected to a pipe in which a gas flows, ~~which tubular body (410; 510; 610) and having~~ has an inlet (411; 511; 611) and an outlet (412; 512; 612) for the flowing gas; the mass flow measurement device comprising means (420; 520; 620) for supplying energy to gas in the tubular body (410; 510; 610), a temperature measurement instrument (460; 560; 660) at the inlet of the tubular body (411; 511; 611), and a temperature measurement instrument (465; 565; 665) at the outlet of the tubular body (412; 512; 612) ~~and a volume percentage measurement instrument (440; 540; 640).~~

17. (new) A mass flow measurement device according to claim 16, wherein the volume percentage measurement instrument (440; 540; 640) is provided in the tubular body (410; 510; 610) downstream of the means (420; 520; 620) for supplying energy to gas in the tubular body (410; 510; 610).

18. (new) A method according to claim 6, wherein the measurement of the volume percentage is made downstream of the supply of a given amount of energy E to the gas in the tubular body (410; 510; 610).